

epoxy-det

01/19 214



EPOXY-DET

Cleaner for epoxy grouting.

**groutings
and sealants**



epoxy-det



APPEARANCE

Yellow liquid

STORAGE

24 months at temperatures from 5° to 30 °C

FIELDS OF USE

- Removal, from ceramic or porcelain stoneware tiling, of light or even heavy residues of epoxy grouting such as: EPOSTUK, SKYCOLORS and SKYCOLORS EVOLUTION.
- Used thinned, it cleans and removes the grease from heavily soiled porcelain stoneware and ceramic floor surfaces.
- Thinned in 1:5 ratio with water, enhances and brightens SKYCOLORS EVOLUTION grouting.

NATURE OF THE PRODUCT

Water-based product. Contains: Less than 5% salts and EDTA, 5% or more soap but less than 15%. Other components: fragrance.

USE

The product should be used either undiluted or diluted with water, as required.

How to remove thick epoxy grouting residues:

pour on the undiluted product. Allow to act for 15-20 minutes, then rub with abrasive felt and rinse off. If necessary, use a metal trowel to remove built up grouting from the tiles, then rub with abrasive felt.

How remove stains left by epoxy grouting or use as dewaxer:

dilute product in 1:5 ratio, apply and allow to act for a few minutes. Rub with felt, or use a scrubbing brush or single-disc cleaner. Vacuum or wipe up dirt and rinse with plenty of water.

Stain removal from porcelain stoneware:

pour undiluted product onto stain and all over tile. Allow to act for 15-20 minutes, then rub with abrasive felt and rinse off.



WARNINGS AND RECOMMENDATIONS

- EPOXY-DET should only be used on epoxy grouting after at least 48 hours have elapsed since grouting was applied; 24 hours if ambient temperature is $\geq 20^{\circ}\text{C}$.
- Do not use on polished marble or stone.
- Do not use on wood.
- Do not use on methacrylate tubs.
- Always test surface to make sure it will not be damaged by EPOXY-DET before using the product.

TECHNICAL DATA	VALUE
Appearance	Liquid
Colour	Yellow
Weight density (g/cm ³)	~ 1.0
pH	~ 11.0

Technokolla reminds you to examine the “**notes**” document that completes the information in this data sheet. The document can be downloaded in the pdf format from the website www.technokolla.com.

The advice about technical matters in the technical data sheets, or given verbally or in writing by our personnel as part of our customer assistance service, is the result of our best and most up to date experience. Since we are unable to personally modify the conditions in the building site or the way the work is carried out, this information is purely indicative and, thus, binds us neither legally nor in any other way in relation third parties. This information does not relieve the end user from being responsible for testing our products so as to make sure they are fit for the required use. We therefore strongly advise the customer/user to subject Technokolla's products to preventive tests in order to ensure that they are suitable. The end user is also responsible for checking to make sure that this technical data sheet is not obsolete and that more recent editions have not replaced it. Thus, before using our products, you are advised to download the most up to date version of the technical data sheet from our web site www.technokolla.com.



Sika Italia S.p.A.

Registered Office and Administrative Headquarters: Via L. Einaudi 6,
20068 Peschiera Borromeo (MI)

Sassuolo Plant (MO): Via Radici in Piano 558, Postal Code 41049

Tel: +39 0536 809711 Fax: +39 0536 809729 www.technokolla.com