

# epoxy-det

02/10 214



## EPOXY-DET

Cleaner for epoxy grouting.

## groutings and sealants

**TECHNOKOLLA**



# epoxy-det



## MAIN FEATURES

### APPEARANCE

Yellow colored liquid

### STORAGE

24 months in a dry place, with temperatures between 5 and 30 °C. Protect against freezing temperatures.

### FIELDS OF USE

- Removal, from ceramic or porcelain stoneware tiling, of light or even heavy residues of epoxy grouting such as: Epostuk, Skycolors and Skycolors Shine.
- Used thinned, it cleans and removes the grease from very dirty floors in porcelain stoneware and ceramic.
- Thinned out with water 1:5 it exalts and gives shiny effect to the gap grouted with SKYCOLORS-SHINE.



### NATURE OF THE PRODUCT

Water-based product. Containing: EDTA and salts less than 5%, soap equal to or greater than 5% but less than 15%. Other components: fragrance.

### USE

The product should be used either undiluted or diluted with water, as required.

#### How to remove consistent epoxy grouting residues:

pour on the undiluted product. Allow to act for 15-20 minutes, then rub with abrasive felt and rinse off. If necessary, use a metal trowel to remove built up grouting from the tiles, then rub with the abrasive felt.

#### How remove the stains left by epoxy grouting or use as a dewaxer:

dilute the product in a ratio of 1:5, apply and allow it to act for a few minutes. Rub with felt, or use a scrubbing brush or single-disc cleaner. Vacuum or wipe up dirt and rinse with plenty of water.

#### To remove stains from porcelain stoneware:

pour the undiluted product on to the stain and all over the tile. Allow the product to act until it has completely dried, then wash and rinse off.



## WARNINGS AND RECOMMENDATIONS

- traces of epoxy grouting should only be removed after at least 48 hours have elapsed since the grouting operation, 24 hours if the ambient temperature is  $\geq 20^{\circ}\text{C}$
- do not use on polished marble or stone
- do not use on wood
- do not use on methacrylate tubs
- test the surface to make sure it is not damaged before applying EPOXY-DET

TECHNICAL SPECIFICATIONS	VALUE
Appearance	Liquid
Colore	Yellow
Weight density (g/cm <sup>3</sup> )	1,01
pH	11,3

**Technokolla** reminds you to examine the “**notes**” document that completes the information in this data sheet.  
The document can be downloaded in the pdf format.

The advice about technical matters and applications in the technical data sheets, or given verbally or in writing by our personnel as part of our customer assistance service, are the result of our best and most up to date experience. Since we are unable to personally modify the conditions in the building site or the way the work is carried out, this information is purely indicative and, thus, binds us neither legally nor in any other way in relation to third parties. This information does not relieve the end user from being responsible for testing our products so as to make sure they are fit for the required use. We therefore strongly advise the customer/user to subject Technokolla's products to preventive tests in order to ensure that they are suitable. The end user is also responsible for checking to make sure that this technical data sheet is not obsolete and that more recent editions have not replaced it. Thus, before using our products, you are advised to download the most up to date version of the technical data sheet from our web site [www.technokolla.com](http://www.technokolla.com).